

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 1 of 6

1. Identification of the substance/mixture and of the company/undertaking

Identification of the substance or mixture

Diesel Fuel Stabilizer 1:1000

Use of the substance/mixture

Multifunction Diesel Fuel Additive

Company/undertaking identification

Company name:	PRO-TEC Deutschland	
Street:	Großgeschwenda 51	
Place:	D-07330 Probstzella	
Telephone:	+4936735/444-0	Telefax: +4936735/444-44
e-mail:	info@pro-tec-deutschland.com	
Contact person:	Jens Möller, Dipl.-Chem.	
Internet:	www.pro-tec-deutschland.de	

Further Information

Article Number: P1281

2. Hazards identification

Classification

Indications of danger : Harmful, Irritant

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Additives

Organic solvents

Corrosion inhibitors.

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 2 of 6

Hazardous components

EC No.	CAS No.	Chemical name	Quantity	Classification
265-149-8	64742-47-8	Distillates (petroleum, gasoline), hydrotreated light	80 - 85 %	Xn R65
	N/A	Aminoethylamid containing Hydroxylalcygroups	5 - 10 %	C R34-43-52
265-191-7	64742-88-7	Solvent naphtha (petroleum, gasoline), medium aliph., Straight run petroleum (gasoline)	1 - 5 %	Xn R10-53-65
202-374-2	N/A	alcylyl aryl amine	1 - 5 %	Xn, Xi R10-22-36-43
	37205-87-1	isonylphenole, ethoxylised phenole, ethoxylised	1 - 5 %	Xn, Xi, N R22-41-51-53
265-198-5	64742-94-5	Naphtha (petroleum)	< 1 %	Xn, Xi, N R10-65-36/38-51-53
202-436-9	95-63-6	1,2,4-trimethylbenzene	< 1 %	Xn, Xi, N R10-20-36/37/38-51-53
203-892-1	111-65-9	octane; n-octane	< 1 %	F, Xn, Xi, N R11-65-38-67-50-53
265-199-0	64742-95-6	Low boiling point naphtha - unspecified, Solvent naphtha (petroleum), light arom.	< 1 %	Xn, Xi, N R10-36-38-51-53-65

Full text of each relevant R phrase can be found in heading 16.

4. First aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .
 Subsequently wash again with: Water and soap.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be swallowed in little sips (dilution effect). Consult physician.

Advice to doctor

Warning about danger of aspiration.

5. Fire-fighting measures

Suitable extinguishing media

Extinguishing powder. Sand. Carbon dioxide (CO₂). alcohol resistant foam.

Extinguishing media which must not be used for safety reasons

High power water jet.

Special exposure hazards arising from substance or mixture itself, combustion products, resulting gases

Formation of decomposition products possible.
 In case of fire and/or explosion do not breathe fumes.

Special protective equipment for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.
 Beat down gas/vapours/mist with water spray.
 Contaminated fire-fighting water must be collected separately.

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 3 of 6

6. Accidental release measures

Personal precautions

Wear a self-contained breathing apparatus and chemical resistant suit.

Keep away from sources of ignition. No smoking.

Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not empty into drains or the aquatic environment.

In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

Methods for cleaning up/taking up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

7. Handling and storage

Handling

Advice on safe handling

Material must only be handled in closed installations or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition. No smoking.

Take precautionary measures against static discharges.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (EH40)

CAS No.	Chemical name	ml/m ³	mg/m ³	F/ml	Category	Origin
95-63-6	Trimethylbenzenes	25	125		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Exposure controls

Protective and hygiene measures

Take off immediately all contaminated clothing

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feeding stuffs.

When using do not eat, drink or smoke.

"Wash hands when done working with material; at breaks, lunch, shift changes, etc."

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 4 of 6

Eye protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

9. Physical and chemical properties

General information

Physical state: liquid
Colour: brown
Odour: characteristic

Important health, safety and environmental information

Test method

Changes in the physical state

Boiling point: 200 - 210 °C
Flash point: > 61 °C
Lower explosion limits: > 0,6 vol. %
Upper explosion limits: > 7,0 vol. %
Ignition temperature: > 200 °C
Vapour pressure: > 8 hPa
(at 20 °C)
Density (at 20 °C): ca. 0.81 g/cm³
Water solubility: insoluble
(at 20 °C)
Solubility in other solvents: Organic solvents

10. Stability and reactivity

Conditions to avoid

Only use material in places where open light, fire and other sources of ignition can be kept away.
No decomposition when used as intended.

Materials to avoid

Oxidizing agents, acid, concentrated. Alkalis (alkalis), concentrated.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Acute toxicity

observations relevant to classification: (LD/LC50-values):

Petroleum (Gasoline)
oral >2000 mg/Kg rat.
dermal >2000 mg/Kg Rabbit.
inhalant > 5 mg/l/4h rat.

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

Sensitizing effects

no danger of sensitization.

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 5 of 6

12. Ecological information

Ecotoxicity

Distillates(petroleum, gasoline)
Fish, LC50, 10-100 mg/l
Algae, IC50, 10-100 mg/l

Bioaccumulative potential

Swims on the water.
Low potential of bio-accumulation.

Further information

Do not empty into drains or the aquatic environment.

13. Disposal considerations

Advice on disposal

Do not dispose with household waste.
Do not empty into drains or the aquatic environment.
Arrange about the exact waste code with the local waste disposal expert.
Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Container must be completely emptied.
Do not pierce, cut up or weld unclean container. (Explosion hazard.)

14. Transport information

Land transport (ADR/RID)

Description of the goods

Not a hazardous material with respect to these transportation regulations.

Inland waterways transport

Description of the goods

Not a hazardous material with respect to these transportation regulations.

Marine transport

Description of the goods

Not a hazardous material with respect to these transportation regulations.

Air transport

Description of the goods

Not a hazardous material with respect to these transportation regulations.

15. Regulatory information

Labelling

Danger symbols:

Xn - Harmful



Xn - Harmful

Hazardous components which must be listed on the label

Distillates (petroleum, gasoline), hydrotreated light

Diesel Fuel Stabilizer 1:1000

Print date: 18.03.2011

Product code: 922

Page 6 of 6

Aminoethylamid containing Hydroxyalcygroups
alcy aryl amine

R phrases

- 36/38 Irritating to eyes and skin.
- 43 May cause sensitization by skin contact.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

S phrases

- 02 Keep out of the reach of children.
- 24 Avoid contact with skin.
- 37 Wear suitable gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.

EU regulatory information

Additional information

- Contains:
- > 30 % aliphatic hydrocarbons
- < 5 % Phenols and halogenated phenols

National regulatory information

Water contaminating class (D): 2 - water contaminating

16. Other information

Full text of R-phrases referred to under sections 2 and 3

- 10 Flammable.
- 11 Highly flammable.
- 20 Harmful by inhalation.
- 22 Harmful if swallowed.
- 34 Causes burns.
- 36 Irritating to eyes.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 36/38 Irritating to eyes and skin.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 43 May cause sensitization by skin contact.
- 50 Very toxic to aquatic organisms.
- 51 Toxic to aquatic organisms.
- 52 Harmful to aquatic organisms.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.
The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)